



D1, synthetic diester based oil, 20 I

D1, synthetic diester based oil, 20 l

- High-quality synthetic diester based oil for standard applications to pump down air, inert, noble and slightly corrosive gases
- Used for high operating temperatures up to max. 120 °C
- Extremely low vapor pressure, achievable ultimate pressure $< 5 \cdot 10^{-2}$ hPa

Technical Data	D1, synthetic diester based oil, 20 l
Achievable ultimate pressure	$< 5 \cdot 10^{-2}$ hPa $< 3.75 \cdot 10^{-2}$ Torr $< 5 \cdot 10^{-2}$ mbar
Operating fluid filling	20 l

Order number	
D1	PK 005 877 -T

VACUUM SOLUTIONS FROM A SINGLE SOURCE

Pfeiffer Vacuum stands for innovative and custom vacuum solutions worldwide, technological perfection, competent advice and reliable service.

COMPLETE RANGE OF PRODUCTS

From a single component to complex systems:

We are the only supplier of vacuum technology that provides a complete product portfolio.

COMPETENCE IN THEORY AND PRACTICE

Benefit from our know-how and our portfolio of training opportunities!

We support you with your plant layout and provide first-class on-site service worldwide.

Are you looking for a
perfect vacuum solution?
Please contact us:

Pfeiffer Vacuum GmbH
Headquarters · Germany
T +49 6441 802-0
info@pfeiffer-vacuum.de

www.pfeiffer-vacuum.com

All data subject to change without prior notice.

PFEIFFER  **VACUUM**