

ANDEROL 794

Synthetic Grease

www.Oil18.ru : 902313@inbox.ru : tel (3412) 902-313

Product Data Sheet



ANDEROL 794 is a diester-based, NLGI number 1.5 grade grease that is formulated to provide clean lubrication for fine instruments and equipment.

APPLICATIONS

- Fine Instruments
- Watches, Clocks and Timing Devices
- Precision Anti-friction Bearings
- Office, Computing and Accounting

COMPATIBILITY

The following seals, paints, and plastics are recommended for use in contact with **ANDEROL** synthetic lubricants. Materials not recommended are also shown. For more information on other materials, see our "Compatibility Guide".

RECOMMENDED:

Viton, High Nitrile Buna N, Teflon, Epoxy Paint, Oil-Resistant Alkyd, Nylon, Delrin, Celcon, PBT.

NOT RECOMMENDED:

Neoprene, SBR Rubber, Low Nitrile Buna N, Acrylic Paint, Lacquer, Polystyrene, PVC, ABS

ADVANTAGES

- Extended lubrication cycles at all temperatures
- Wide temperature application -65° to 300° F
- Resistant to oil bleed

PROPERTIES	TEST METHOD	ANDEROL 794
NLGI Number	---	1.5
Worked Penetration, mm	ASTM D-217	315
Worked Stability, 100,000 strokes, mm	ASTM D-217	335
Base Oil Viscosity @ 40° C, cSt	ASTM D-445	13.5
Base Oil Viscosity @100° C, cSt	ASTM D-445	3.6
Base Oil Viscosity Index (VI)	ASTM D-2270	159
Dropping Point, ° C	ASTM D-566	177
Oil Separation, 30 hr. @ 100° C	ASTM D-6184	6.0
Four-Ball War, 1200 rpm, 40kg, 1 hr, mm @ 75° C	ASTM D-2266	0.6
Specific Gravity, 60 ° F (15.6° C)	ASTM D-1480	0.94
Density, lbs/gallon	ASTM D-1250	7.83

FOR MORE INFORMATION PLEASE REFER TO THE RELEVANT MATERIAL SAFETY DATA SHEET

APPROVALS / REGISTRATIONS



ANDEROL BV

Punterweg 21 A
6222 NW MAASTRICHT
The NETHERLANDS
Tel No.: +31 (0)43 352 41 90
Fax No.: +31 (0)43 352 41 99
www.anderol-europe.com

This information is furnished without warranty, representation, inducement, or license of any kind except that it is accurate to the best of OUR knowledge or obtained from sources believed by ANDEROL to be accurate. ANDEROL does not assume any legal responsibility for use of reliance upon it. Only Chemists or chemically qualified lab technicians should carry out tests. Before using any chemicals, read its label and Material Safety Data Sheet.