# ANDEROL FG XL 32 www.Oil18.ru : 902313@inbox.ru : tel (3412) 902-313

**H1 High Performance Food Grade Compressor Lubricant** 

**Product Data Sheet** 



**ANDEROL FG XL 32** is a next generation synthetic compressor oil based on a mixture of specially selected non-toxic synthetic polyalphaolefins combined with a high performance additive technology. This advanced formulation provides additional detergency properties preventing lacquer and varnish formation.

**ANDEROL FG XL 32** meets the lubrication requirements of air compressors running in food processing plants.

ANDEROL FG XL 32 meets or exceeds DIN 51506.

**ANDEROL FG XL 32** is NSF/H1 and InS/H1 registered. The product is certified Kosher by the Orthodox Union and Halal by the Islamic Food Council of Europe.

### **ADVANTAGES / BENEFITS**

- Fewer oil changes
- Compatible with compressor seals, gaskets, hoses and system components
- Reduced varnish, lacquer and deposits
- Less maintenance intervals
- Lower oil consumption
- Excellent anti-wear properties
- Rust and oxidation inhibited
- Good water separation

## **COMPATIBILITY**

ANDEROL synthetic hydrocarbon based lubricants are similar to mineral oils in their compatibility with paints, seals, gaskets and hoses. No special precautions related to compatibility are required when changing over from a mineral oil lubricant to an ANDEROL synthetic hydrocarbon based lubricant.

This product was tested and found compatible to be used in ammonia systems.

### **APPLICATION**

Recommended for use in rotaryscrew compressors and other rotating equipment applications where incidental food contact may occur.

Nominal Operating Range is -35/-40°C to 170°C.

PROPERTIES	TEST METHOD	ANDEROL FG XL 32
Appearance @ 20°C Viscosity @ 40°C, cSt Viscosity @ 100°C, cSt Viscosity Index Density @ 15°C, kg/I Total Acid Number, mg KOH/g Flash Point, COC, °C Pour Point, °C Demulsibility @ 54°C, min	Visual ASTM D-445 ASTM D-445 ASTM D-2270 ASTM D-1298 ASTM D-664 ASTM D-92 ASTM D-97 ASTM D-1401	Clear colorless to light yellow liquid 34.5 6.3 135 0.832 0.09 235 -57 10

FOR MORE INFORMATION PLEASE REFER TO THE RELEVANT MATERIAL SAFETY DATA SHEET

## **APPROVALS / REGISTRATIONS**

















ANDEROL BV Punterweg 21 A 6222 NW MAASTRICHT The NETHERLANDS

Tel No.: +31 (0)43 352 41 90 Fax No.: +31 (0)43 352 41 99 www.anderol-europe.com