



ANDEROL HTFG 2 is a high temperature polytetrafluor ethylene concentrate (PTFE) thickened grease based on synthetic oil.

ANDEROL HTFG 2 is chemical resistant and provides lubrication at temperatures up to 300°C. It is NSF (H1) registered for use in applications where incidental food contact might occur.

APPLICATIONS / ADVANTAGES

- Food Grade High Temperature Grease
- Applications where Elastomer compatibility is a must
- Temperature charged conveyors
- Baking Ovens
- Drying, lacquering and enamelling furnaces
- Tunnel furnace trolleys
- Hot gas fans
- Textile tenter frames, foil stretching machines
- Valves and fittings for Oxygen (up to 60°C and pressure limit of 100 bar)
- Bicycle shifters, Bicycle suspension
- Fishing reels
- CD/DVD drives (main bearing)

REGISTRATIONS / APPROVAL

ANDEROL Lubricants are approved, recommended and field tested by many OEM's in the Food processing, bottling, canning, meat processing and pharmaceutical industries.

HANDLING AND STORAGE

ANDEROL lubricants generally present little hazard in normal handling if ordinary care is exercised. If spilled, cover with inert, absorbent material and remove. Flush the area with water.

Although **ANDEROL** lubricants are not highly flammable, they will burn and should be kept away from open flames. In case of fire, use water spray, foam, carbon dioxide, or dry chemical.

ANDEROL lubricants should be stored preferably in protected locations to prevent contamination. Do not re-use drums; flush and send to re-conditioner.

PROPERTIES	TEST METHOD	ANDEROL HTFG-2
Thickener		PTFE
Color		White
Type of Base Oil		Synthetic (PFPE)
Operating temperature for long-term lubrication, °C		-40 to 280 °C
Short term admissible temperature peak value, °C		+300°C
Dropping Point, °C		Not dropping
Worked Penetration		265 to 295 0.1 mm
Base Oil Viscosity at 40°C		Approx. 500 mm ² /s
Water resistance		0-90
4-ball weld load		3600 N
Designation		KFK 2 U-40
	DIN ISO 2176	
	DIN ISO 2137	
	DIN 51.562	
	DIN 51.807-01	
	DIN 51.350/4	
	DIN 51.502	

FOR MORE INFORMATION PLEASE REFER TO THE RELEVANT MATERIAL SAFETY DATA SHEET

APPROVALS / REGISTRATIONS



ANDEROL BV
 Punterweg 21 A
 6222 NW MAASTRICHT
 The NETHERLANDS
 Tel No.: +31 (0)43 352 41 90
 Fax No.: +31 (0)43 352 41 99
 www.anderol-europe.com