



**ANDEROL PQAA-150** is a white oil based H1 registered lubricant, combined with high performance additives. They are designed to provide outstanding lubrication protection to gear sets, bearings and pump in applications in the Food Industry.

Anderol PQAA range is available in the grades ISO VG 150, 220, 320, 680 & 1000 .

**ANDEROL PQAA-150** is NSF/H1 and InS/H1 registered. The product is certified Kosher by the Orthodox Union and Halal by the Islamic Food Council of Europe.

**ANDEROL** Food Grade Lubricants meet the requirement of the FDA regulation 21 CFR 178.3570

### ADVANTAGES / BENEFITS

- Product was developed with highly stable white oil
- Product has excellent wear and load carrying capacity
- Rust and oxidation inhibited
- Good water separation

### COMPATIBILITY

**ANDEROL** white oil based lubricants are similar to mineral oils in their compatibility with paints, seals, gaskets and hoses. No special precautions related to compatibility are required when changing over from a mineral oil lubricant to this product.

### APPLICATIONS

H1 Food Approved gear lubricant suitable for food manufacturing applications where incidental food contact may occur.

Recommended for use in:

- Chain lubrication
- Bearings and gears
- Wipe down oil
- Worm gear applications

### APPROVALS

- Unilever

PROPERTIES	TEST METHOD	ANDEROL PQAA 150
Appearance @ 20°C	Visual	Clear Yellow Liquid
Viscosity @ 40°C, cSt	ASTM D-445	158
Viscosity @ 100°C, cSt	ASTM D-445	16.3
Viscosity Index	ASTM D-2270	108
Density @ 15°C, kg/l	ASTM D-1298	0.862
Total Acid Number, mg KOH/g	ASTM D-664	1.3
Flash Point, °C	ASTM D-92	217
Pour Point, °C	ASTM D-97	-15
Demulsibility @ 54°C,min	ASTM D-1401	15

FOR MORE INFORMATION PLEASE REFER TO THE RELEVANT MATERIAL SAFETY DATA SHEET

### APPROVALS / REGISTRATIONS



**ANDEROL BV**  
 Punterweg 21 A  
 6222 NW MAASTRICHT  
 The NETHERLANDS  
 Tel No.: +31 (0)43 352 41 90  
 Fax No.: +31 (0)43 352 41 99  
[www.anderol-europe.com](http://www.anderol-europe.com)