



ANDEROL PQAA 22 is a white oil based H1 registered general purpose lubricant, combined with high performance additives. It meets most general purpose requirements of machinery. Anderol PQAA range is available in the grades ISO VG 22 , 32 , 46 , 68 , 100 & 150 .

ANDEROL PQAA 22 is NSF/H1 and InS/H1 registered. The product is certified Kosher by the Orthodox Union and Halal by the Islamic Food Council of Europe.

ANDEROL Food Grade Lubricants meet the requirement of the FDA regulation 21 CFR 178.3570

ADVANTAGES / BENEFITS

- Product was developed with highly stable white oil
- Product has excellent wear and load carrying capacity
- Rust and oxidation inhibited
- Good water separation

COMPATIBILITY

ANDEROL highly refined oil based lubricants are similar to mineral oils in their compatibility with paints, seals, gaskets and hoses. No special precautions related to compatibility are required when changing over from a mineral oil lubricant to this product

APPLICATIONS

H1 Food Approved general purpose lubricant suitable for food manufacturing applications where incidental food contact may occur.

Recommended for use in:

- Hydraulic systems and slide ways
- Pneumatic tools
- Wipe down oil

Can generally be used in all other rotating equipment applications.

APPROVALS

- Unilever

PROPERTIES	TEST METHOD	ANDEROL PQAA 22
Appearance @ 20°C	Visual	Clear liquid
Viscosity @ 40°C, cSt	ASTM D-445	23.7
Viscosity @ 100°C, cSt	ASTM D-445	4.5
Viscosity Index	ASTM D-2270	101
Density @ 15°C, kg/l	ASTM D-1298	0.8642
Total Acid Number, mg KOH/g	ASTM D-664	0.7
Flash Point, COC, °C	ASTM D-92	182
Pour Point, °C	ASTM D-97	-9
Demulsibility @ 54°C,min	ASTM D-1401	5

FOR MORE INFORMATION PLEASE REFER TO THE RELEVANT MATERIAL SAFETY DATA SHEET

APPROVALS / REGISTRATIONS



ANDEROL BV

Punterweg 21 A

6222 NW MAASTRICHT

The NETHERLANDS

Tel No.: +31 (0)43 352 41 90

Fax No.: +31 (0)43 352 41 99

www.anderol-europe.com