



**ANDEROL PQAA 32** is a white oil based H1 registered general purpose lubricant, combined with high performance additives. It meets most general purpose requirements of machinery. Anderol PQAA range is available in the grades ISO VG 32 , 46 , 68 , 100 .

**ANDEROL PQAA 32** is NSF/H1 and InS/H1 registered. The product is certified Kosher by the Orthodox Union and Halal by the Islamic Food Council of Europe.

**ANDEROL** Food Grade Lubricants meet the requirement of the FDA regulation 21 CFR 178.3570

### ADVANTAGES / BENEFITS

- Product was developed with highly stable white oil
- Product has excellent wear and load carrying capacity
- Rust and oxidation inhibited
- Good water separation

### COMPATIBILITY

**ANDEROL** white oil based lubricants are similar to mineral oils in their compatibility with paints, seals, gaskets and hoses. No special precautions related to compatibility are required when changing over from a mineral oil lubricant to this product.

### APPLICATIONS

H1 Food Approved general purpose lubricant suitable for food manufacturing applications where incidental food contact may occur.

Recommended for use in:

- Hydraulic systems and slide ways
- Vacuum pumps and compressors
- Chain lubrication
- Bearings and gears
- Wipe down oil

Can generally be used in all other rotating equipment applications

### APPROVALS

- Unilever

PROPERTIES	TEST METHOD	ANDEROL PQAA 32
Appearance @ 20°C	Visual	Clear liquid
Viscosity @ 40°C, cSt	ASTM D-445	34.3
Viscosity @ 100°C, cSt	ASTM D-445	5.7
Viscosity Index	ASTM D-2270	105
Density @ 15°C, kg/l	ASTM D-1298	0.862
Total Acid Number, mg KOH/g	ASTM D-664	0.6
Flash Point, COC, °C	ASTM D-92	186
Pour Point, °C	ASTM D-97	-9
Demulsibility @ 54°C,min	ASTM D-1401	20

FOR MORE INFORMATION PLEASE REFER TO THE RELEVANT MATERIAL SAFETY DATA SHEET

### APPROVALS / REGISTRATIONS



**ANDEROL BV**  
 Punterweg 21 A  
 6222 NW MAASTRICHT  
 The NETHERLANDS  
 Tel No.: +31 (0)43 352 41 90  
 Fax No.: +31 (0)43 352 41 99  
 www.anderol-europe.com

