



Product Data

Castrol Flexiclean

Heavy duty, multi-purpose alkaline cleaner

Description

Castrol Flexiclean™ is an aqueous, alkaline industrial multi-purpose cleaner containing biodegradable surfactants and corrosion inhibitors. The product is free of strong complexing agents.

Application

Flexiclean is a versatile product, being suited to a very wide range of operations in production engineering, as well as being suitable for virtually all ferrous and non-ferrous metals.

Flexiclean can be used for:

- Industrial process cleaning in wide range of modern equipment, which includes spray and flood wash as well as dip and ultrasonic applications, capable of removing difficult soils, such as heavy duty neat cutting or forming oils, greasy and waxy corrosion preventive films, lubrication oils and greases, carbon as well as swarf and general workshop grime.
- Machine tool cleaning of central systems, individual sumps, and other contaminated areas of machine tools. It is suitable for use with all types of soluble metalworking fluids including synthetics. Added to the system on the day before the coolant is due to be discharged will ensure thorough cleaning by the time the entire coolant system is emptied the following day.
- General purpose maintenance cleaning on floors, walls and other hard surfaces.
- Mass vibratory finishing in conjunction with abrasive stones (MVF).

Conditions of Use

	Spray / Flood wash	Dip / Ultrasonic	Maintenance cleaning & MVF
Concentration Range:	up to 10%	up to 20%	0.5 - 2%
Temperature Range:	up to 80°C / 176°F	up to 80°C / 176°F	ambient

Optimum conditions of use are depending on the detailed application requirements and the amount and nature of the soil being removed.

Advantages

- Strong, alkaline but multi-metal compatible cleaner, that does not affect suitably painted surfaces of machine tools, equipment, and industrial surfaces including cement and plastics – minimises scrap rate which improves productivity.
- Low foaming at ambient temperature, which allows for initial cold water start ups – economical, improves productivity at lower costs
- Free of strong complexing agents – does not harm subsequent waste water treatment
- Versatile, can be used in various applications and is suitable in hard and soft water – enables possible product consolidation

Typical Characteristics

	Test Method	Unit	Value
Appearance	Visual	-	Clear brown liquid
Density @ 20°C	IP 160	kg/m ³	1150
Density @ 68°F	IP 160	lb/gal	9.6
pH (2% solution)	BS 1647	-	11.5
Total alkalinity	BAM 101	% NaOH	11

User Advice

Flexiclean is suitable for multi-metal cleaning, however we recommend that yellow metals should be rinsed with clean water to remove any alkaline residues.

Castrol, Flexiclean, and the Castrol logo are trademarks of Castrol Limited, used under licence

INTERNATIONAL All reasonable care has been taken to ensure that the information contained in this publication is accurate as of the date of printing. However, such information may, nevertheless, be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol Ltd products. The MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product.

Castrol Limited, Pipers Way, Swindon, Wiltshire SN3 1RE, UK
www.castrol.com/industrial

Castrol Flexiclean
10 October 2008 Version 1