

Product Data

Castrol Obeen FS 2

Physiologically safe special grease

Description

OBEEN FS 2 is a physiologically safe, fully synthetic (free from mineral oil), special grease.

It is especially suited for the food, beverage and pharmaceutical industries where there might be a direct contact between the lubricant and the foodstuff or its packaging.

OBEEN FS 2 only contains raw materials which are listed in the Guideline of Security 21

CFR 178.3570 of the FDA and which are in conformity with NSF H1.

Application

- As bearing grease in the food industry for the lubrication of rolling and sliding bearings, above all at high speeds in fillers, closing machines etc. as well as various household appliances and machines in the pharmaceutical and cosmetic industries.

Advantages

- OPTITEC™ - CASTROL OPTIMOL technology
- physiologically safe
- tasteless and odorless
- good adhesion
- resistant to hot and cold water
- excellent resistance to cleaning agents and disinfectants
- compatible with sealing materials resistant to mineral oil
- temperature application range: - 30°C/- 22°F to + 140°C/+ 284°F
- good behavior at low temperatures

Typical Characteristics

Test	Method	Unit	Value
CASTROL OBEEN FS	-	-	2
Colour	visual	-	amber
Base	-	-	Al-complex/PAO
Consistency/NLGI grade	DIN 51818	-	2
Worked penetration	DIN ISO 2137	0.1 mm	289
Density at + 20°C/+ 68°F	DIN 51757	kg/m ³	835.4
Dropping point	DIN ISO 2176	°C	> 230
		°F	> 446

1 mm²/s $\hat{=}$ 1cSt

Subject to usual manufacturing tolerances

Additional Information

- Please observe the specifications of the plant and machine manufacturers.
- OBEEN FS 2 is not suited for the lubrication of seals made of EPDM materials

Castrol, Obeem, and the Castrol logo are trademarks of Castrol Limited, used under licence

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet.

It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Limited, Pipers Way, Swindon, Wiltshire SN3 1RE, UK
www.castrol.com/industrial