



## Product Data

# Castrol Techniclean XHD

Heavy duty, strongly alkaline process cleaner

## Description

Castrol Techniclean™ XHD is an aqueous, strong alkaline industrial cleaner. The product is free of silicates and strong complexing agents.

## Application

Techniclean XHD is designed to remove heavy soils that are difficult to remove with more neutral products, such as heavy duty neat cutting or forming oils, greasy and hard film corrosion preventives, lubrication oils and greases as well as swarf, carbon, rust and paint. The product is also often used in re-conditioning workshops and when a high level of cleanliness is required. Techniclean XHD is can be used in wide range of modern equipment, which includes spray and intensive flood wash as well as dip and ultrasonic applications.

## Conditions of Use

Concentration Range:	1 - 5%
Temperature Range:	40 - 70 °C
Spray Pressure:	up to 20 bar

Optimum conditions of use are depending on the detailed application requirements and the amount and nature of the soil being removed.

## Advantages

- Strong, alkaline cleaner, removes heavy soils – improves parts quality and reduces scrap rate
- Silicate-free, minimises the amount of solid residues within the cleaning equipment – increases productivity due to possible reduction of maintenance work and extension of bath changing intervals
- Free of strong complexing agents – improves the quality of subsequent processes, such as etching baths or waste water treatment
- Emulsified oil separates on standing and can be skimmed off in order to increase bath-life – reduces maintenance and disposal cost.
- Low foaming at ambient temperature, which allows for initial cold water start ups – economical, improves productivity at lower costs
- Versatile, can be used in various applications and is suitable in hard and soft water – enables possible product consolidation

## Typical Characteristics

	Test Method	Unit	Value
Appearance	Visual	-	Clear, amber liquid
Density @ 20°C	IP 160	kg/m <sup>3</sup>	1330
pH (5% solution)	BS 1647	-	13,1
Total alkalinity	BAM 101	% NaOH	23

## Storage

To avoid product deterioration, keep the container/drum tightly sealed always. Prevent any frost and water ingress.

Store it in a cool and dry place away from direct sunlight. It is preferable to store the product indoors always.

For more details, please refer the product safety data sheet.

Castrol, Techniclean (Lettered), and the Castrol logo are trademarks of Castrol Limited, used under licence

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet.

It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material.

All products, services and information supplied are provided under our standard conditions of sale.

You should consult our local representative if you require any further information.

Deutsche BP AG – Industrial Lubricants & Services, Erkelenzer Str. 20, 41179 Mönchengladbach

Tel: +49 (0)2161 909-30 Fax: +49 (0)2161 909-481

[www.castrol.com](http://www.castrol.com)