



Product Data

Castrol Tribol® 1100 Gear Oils

(With TGOA)

Castrol Tribol® 1100 Gear Oils with the TGOA additive system represent a significant advancement in gear oil technology. Developed for service in enclosed gear drives, journals, and antifriction bearings, **Castrol Tribol® 1100 Gear Oils** are typically used where heavy and shock load conditions prevail.

Description

Castrol Tribol® 1100 Gear Oils are manufactured from the highest quality petroleum base oils. Blended into this oil is the latest development in the field of surface improving additives designated TGOA. TGOA is an oil soluble additive package designed to reduce friction while providing surface protection and improvement. The TGOA additive package offers superior performance because of its unique action on frictional surfaces.

TGOA works by establishing a highly protective metal rich lubricating film. This film is formed by the reaction of TGOA additives due to frictional heat and the catalytic action of metallic surfaces. The results are a smoothing of surface roughness without creating abrasion. Therefore, surface roughnesses are reduced without the usual loss of surface material.

The results of the TGOA process can be compared with a rolling process in the micro-range. The surface roughnesses are gradually leveled and smoothed. Through this smoothing action, the actual load-bearing area is enlarged with the loads being distributed over increasing areas. Therefore the actual load per unit of working area decreases.

If surface roughness peaks redeveloped because of shock loads or stop-and-go operation, the TGOA additive package is automatically reactivated. Surface roughnesses are again smoothed and lubrication optimized.

Castrol Tribol® 1100's have passed the harsh Cincinnati Milacron Thermal Stability Test. This test evaluates copper and steel corrosion and oxidation stability. **Castrol Tribol® 1100 Gear Oils** are approved as P 74, P 59, and P 35 for the ISO 220, 320, and 460 grades respectively.



Product Data

Applications

Typical applications are spur, helical, herringbone, bevel, and planetary gears. They are also used in general couplings and where fine filtration is required.

Castrol Tribol® 1100 Gear Oils may be used in antifriction and journal bearings and applied by oil mist systems.

Castrol Tribol® 1100 Gear Oils with the TGOA additive package are most effective when used from the initial fill of the equipment. It has also proven to be effective in applications where surfaces have previously been damaged in service.

Advantages

Because of TGOA's highly protective lubricating film the following advantages can be obtained:

- Reduced friction
- Reduced wear
- Lower operating temperature
- Lower noise level
- Reduced pitting if not caused by design or heavy overloading

As a result of the TGOA advantage the following benefits can be derived:

- Longer gear and bearing life
- Reduced maintenance costs
- Greater productivity
- Higher profitability

Notes

Castrol Tribol® 1100 Gear Oils are compatible with other petroleum gear oils. This means that traces of previous oil remaining in the gearcase after draining should not pose problems. However, the beneficial effects of the TGOA additives are reduced when **Castrol Tribol® 1100 Gear Oils** are mixed with other oils. A thorough cleaning of the gearbox is highly recommended to achieve the maximum benefits of **Castrol Tribol® 1100 Gear Oils**.

For specific terms, conditions, warranty, and availability, refer to Castrol Performance Lubricants' Price List in effect at time of purchase



Product Data

Typical Characteristics

	1100/68	1100/100	1100/150	1100/220	1100/320	1100/460	1100/680	1100/1000	1100/1500
ISO Viscosity Grade, ASTM D 2422	68	100	150	220	320	460	680	1000	1500
AGMA Lubricant Number	2EP	3EP	4EP	5EP	6EP	7EP	8EP	8AEP	--
Food Grade	H2	H2	H2	H2	H2	H2	H2	H2	--
Specific Gravity, @ 60°F ASTM D 1298	0.89	0.89	0.89	0.89	0.89	0.89	0.90	0.91	0.93
API Gravity, ASTM D 1298, @ 15.6°C	27.1	26.5	25.5	24.9	23.4	23.0	20.8	18.8	18.0
Viscosity, ASTM D 445, D 2161:									
@ 40°C, mm ² /s (cSt)	68	100	150	220	320	460	680	1000	1500
@ 100°C, mm ² /s (cSt)	9.0	11.6	15.3	19.7	25.0	30.6	38.3	52.5	64.8
@ 100°F, cSt/SUS	76/352	112/519	170/788	250/1158	367/1700	532/2464	794/3677	1170/5420	1775/8220
@ 210°F, cSt/SUS	9.2/56	11.9/66	15.8/81	20.3/100	25.8/124	31.7/150	39.7/187	54.5/254	67.5/315
Viscosity Index, ASM D 2270	106	104	103	102	102	96	93	100	96
Flash Point, ASTM D 92, COC, °C/°F	232/450	232/450	240/465	240/465	240/465	240/465	240/465	246/475	246/475
Pour Point, ASTM D 97, °C/°F	-26/-15	-23/-10	-23/-10	-20/-5	-18/0	-15/+5	-12/+10	-10/+15	-10/+15
Rust Test, ASTM D 665:									
Procedure A (Distilled Water)	Pass	Pass	Pass	Pass	Pass	Pass	Pass	Pass	Pass
Procedure B (Synthetic Sea Water)	Pass	Pass	Pass	Pass	Pass	Pass	Pass	Pass	Pass
Copper Corrosion Test, ASTM D 130									
3 hrs, 100°C	1a	1a	1a	1a	1a	1a	1a	1a	1a
Timken Extreme Pressure Test ASTM D 2782									
OK Value, kg/lbs	27/60	32/70	32/70	34/75	34/75	34/75	34/75	34/75	32/70
Four Ball Wear Test (40 kg, 75°C/167°F, 1800 rpm, 1 hr)									
Scar Diameter, mm	0.40	0.40	0.40	0.40	0.40	0.40	0.40	0.40	0.40
Falex Wear Test, ASTM D 2670									
Wear Teeth	5	5	5	5	5	5	5	5	5
SRV Test, 50°C 300N 2 hr DIN E51843-02-5									
Amplitude 1 mm, Frequency 50 Hz (μ = coefficient of friction)	----- μ = 0.07 – 0.09 -----								
FZG Test, DIN 51354									
(A/8.3/90) IP 334	>12	>12	>12	>12	>14	>12	>12	>12	>12
Visual Inspection	-- GEAR TOOTH FLANKS LIKE NEW --								

For further product information, please contact Divisional Engineering.

Subject to usual manufacturing tolerances.

All reasonable care has been taken to ensure that this information is accurate as of the date of printing. Nevertheless, such information may be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol products. The MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product.