





## Advantages

- Good thermal and oxidative stability provides reliable operation and extended operating life when compared to mineral oil based products.
- Inherently high viscosity index makes the product suitable for operations operating over a wide temperature range.
- Good anti-wear and load carrying abilities including FZG >12 rating under A1 6.6/110 test conditions eliminates wear and prolongs gear tooth life.
- Good water separation and demulsification characteristics means reduced down time through prolonged lubricant life and increased equipment reliability.
- PAO based lubricant provides good compatibility with seals, paints and mineral oil based lubricants.

## Additional Information

Alphasyn HTX range is classified as non-hazardous according to the criteria of Safe Work Australia. For further information please refer to separate Material Safety Data Sheet available on request. It is a non-Dangerous Good.

Alphasyn HTX range is classified as C2 combustible according to AS 1940 for storage and handling purposes.

Spillage: **SMALL - 20 LITRES OR LESS**

Soak up on Castrol Diatomaceous Earth or similar inert oil absorbent. Arrange for disposal through an approved facility.

**LARGE - GREATER THAN 20 LITRES**

Contain as soon as possible, remove by best means available and arrange recycling (preferred) or disposal through an approved facility.

Disposal: New or used material must not be allowed to enter the ground, ground water, water courses, sewers or drainage systems. Advice may be sought from the Environmental Protection Authority or from the local waste disposal authority

Castrol, Alphasyn HTX and the Castrol logo are trademarks of Castrol Limited, used under license.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet.

It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. See [www.msds.castrol.com.au](http://www.msds.castrol.com.au) No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Australia Pty Limited, GPO Box 5222, Melbourne VIC 3001  
Technical Advice Line 1300 557 998 / Customer Service 1300 722 088  
[www.castrol.com/industrial](http://www.castrol.com/industrial)