



## Product Data

# Castrol Rustilo® 4130

Solvent-Based Water-Displacing Corrosion Preventive

### Description

**Castrol Rustilo 4130** is a solvent-based, water-displacing corrosion preventive formulated to give excellent long term, indoor protection. This product deposits a thin, slightly greasy residual film, which is easily cleaned using an alkaline cleaner or vapor degreaser.

### Performance Benefits

- When used straight, this product will provide excellent humidity protection for ferrous and nonferrous parts for up to 18 months indoor storage.
- When used straight, a single coat of **Castrol Rustilo 4130** will provide excellent resistance to acid atmospheres for ferrous and nonferrous parts which have been stored in or near acid environments.
- Displaces freestanding water and cleaner solution, and replaces the water with a protective oil film.

### Use Castrol Rustilo 4130 where:

- Previous operations expose the metal to water-containing machining and grinding coolants, cleaners, or water rinses.
- Long term indoor humidity protection is needed.
- Protection against an acid atmosphere is needed.
- Ease of cleanability is desired.

### Recommended Applications & Dilutions

For best results, **Castrol Rustilo 4130** should be applied by dipping, especially if water displacement is needed. Spraying or flowcoating is also acceptable if properly functioning.

#### Castrol Industrial Americas

150 W. Warrenville Road,  
Naperville, IL 60563  
Tel (877) 641 1600  
Fax (877) 648 9801



## Product Data

### Typical Characteristics

Appearance: Clear to hazy amber fluid  
Specific Gravity @ 60°F (16°C): 0.81 - 0.83  
Viscosity, SUS @ 100°F (38°C): 33  
Bulk Density (lbs/gal): 6.8  
Flash Point, COC: 150°F (68°C) Minimum  
Fire Point, COC: 160°F (71°C) Minimum  
Film Type: Slightly greasy  
Suppressor: Yes  
Neutralizer: No  
Water Displacement: Yes

All reasonable care has been taken to ensure that the information contained in this publication is accurate as of the date of printing. However, such information may, nevertheless, be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol Industrial North America Inc. products. The MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product.

### Castrol Industrial Americas

150 W. Warrenville Road,  
Naperville, IL 60563  
Tel (877) 641 1600  
Fax (877) 648 9801