



Product Data

Castrol Rustilo[®] DWX 30

Description

A mobile dewatering fluid on evaporation of the solvent deposits an ultra-thin protective film.

Film Characteristics

Very thin, slightly greasy.

Recommended Applications

This product affords an ultra-thin protective film which does not interfere with air-gauging equipment. It has excellent water-displacing, demulsification and protective properties, and contains a fingerprint neutralizing agent. The ultra-thin film gives excellent rust preventive properties for inter-operational protection.

It has also been used as a mild pressworking lubricant when it gives protection to the workpiece without additional treatment.

Method Of Use

Preferably by immersion but where impractical the fluid may be applied by brushing or spraying.

Protection

Indoors - 9 months

Outdoors - 3 months

The period specified for outdoor use assumes primary protection from the elements by tarpaulin or another form of cover.

Castrol Industrial

Premier Lubricants (S) Pte Ltd
24 Jurong Port Road,
#01-01 Office Block,
CWT Distripark, Singapore 619097
Tel.: +65 262 5561
Fax: +65 262 5560

Removal

Normally not necessary but if required, petroleum solvents or suitable alkaline cleaner.

Advantages

A particular feature of this product is its ability to suppress the corrosion attack that may be caused by fingerprints, which is particularly important to the protection of highly finished surfaces.

Typical Characteristics

Castrol	Rustilo [®] DWX 30
Appearance	Light Brown Fluid
Density @ 15°C	0.79
Flash Point (Abel)	40°C minimum
Coverage (approx.)	105.0 m ² / litre
Film Thickness (approx.)	0.64 microns
Film Density (approx.)	0.62 gm/ m ²
Drying Time @ 21°C (to 95% solvent loss)	30 mins.

All reasonable care has been taken to ensure that the information contained in this publication is accurate as of the date of printing. However, such information may, nevertheless, be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol Industrial North America Inc. products. The MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product.

July 2003 (Version 01)

Castrol Rustilo[®] DWX 30

Page 2 of 2