



**ANDEROL 2150 HTCL** is an ISO 150 synthetic ester based chain lubricant specifically designed to provide longterm lubrication even under severe heavy duty and extreme ambient conditions.

**ANDEROL 2150 HTCL** prevents wear, noise, sticking by means of :

- Film reformation between loadings
- Removal of frictional heat
- Flushing of wear debris
- Excellent corrosion and rust protection

The HTCL range is available in the grades ISO VG 100 , 150 , 220 , 320 and 460

### ADVANTAGES / BENEFITS

ANDEROL synthetic Chain lubricants are the only long-life synthetic lubricants with over 60 years of successful performance.

- Protects against external and internal wear
- Very good drive lubrication
- Lower oil consumption
- Oil film stays well maintained
- Reduces energy consumption & cost

### COMPATIBILITY

The following seals, paints and plastics are recommended for use in contact with Anderol Synthetic Lubricants. Materials not recommended are also shown. For more information on other materials see our 'Compatibility Guide'.

#### RECOMMENDED :

Viton, High Nitrile Buna N, Teflon, Epoxy Paint, Oil-Resistant Alkyd, Nylon, Delrin, Celcon, PBT

#### NOT RECOMMENDED:

Neoprene, SBR Rubber, Low Nitrile Buna N, Acrylic Paint, Lacquer, Polystyrene, PVC, ABS

### APPLICATION

Recommended to be used in difficult environments and conditions including:

- Pulsating, heavy loads and/or high speeds
- Grit , dust , acids and moisture
- High temperature

The **2150 HTCL** can be applied by

- Brush
- Manually
- Oil bath
- Pressurized system

Nominal Operating Range up to 250 °C

PROPERTIES	TEST METHOD	ANDEROL 2150 HTCL
Appearance @ 20°C	visual	Clear Yellow Liquid
Viscosity @ 40°C, cSt	ASTM D-445	142.0
Viscosity @ 100°C, cSt	ASTM D-445	17.6
Viscosity Index	ASTM D-2270	137
Density @ 15°C, kg/l	ASTM D-1298	0.921
Total Acid Number, mg KOH/g	ASTM D-664	0.3
Flash Point, °C	ASTM D-92	265
Pour Point, °C	ASTM D-97	-40

FOR MORE INFORMATION PLEASE REFER TO THE RELEVANT MATERIAL SAFETY DATA SHEET

### APPROVALS / REGISTRATIONS



#### ANDEROL BV

Punterweg 21 A  
6222 NW MAASTRICHT  
The NETHERLANDS

Tel No.: +31 (0)43 352 41 90

Fax No.: +31 (0)43 352 41 99

www.anderol-europe.com