

ANDEROL 5150 XEP

Synthetic Gear and Bearing Lubricant

www.Oil18.ru : 902313@inbox.ru : tel (3412) 902-313

Product Data Sheet



ANDEROL 5150 XEP is a synthetic based, high performing gear lubricant to be used in industrial equipment. It was designed to withstand heavy loads and severe conditions resulting in very good micropitting resistance. The PAO based product gives superior advantages to the mineral oil based products, especially with regards to low pour point, oxidation stability and energy consumption.

ANDEROL 5000 XEP range is available in the grades ISO VG 150, 220, 320, 460, 680 and 1000. Meets or exceeds the requirements of:

ANSI/AGMA 9005 (table 3)
AISE 224 (formerly USS 224)
DIN 51.517
Cincinnati P-59

ADVANTAGES / BENEFITS

- Excellent oxidation and thermal stability
- Wide operating temperature range
- Lower maintenance costs
- Excellent load carrying ability
- Extended lubricant life
- Improved cleanliness
- Excellent anti wear & EP properties
- Very good rust and copper corrosion prevention
- Compatible with petroleum oils, therefore allowing minimal effort to changeover

APPROVALS

- Flender
- Rossi Motoriduttori

COMPATIBILITY

The following seals, paints and plastics are recommended for use in contact with Anderol Company Synthetic Lubricants. Materials not recommended are also shown. For more information on other materials see our 'Compatibility Guide'.

RECOMMENDED :

Viton, High Nitrile Buna N, Teflon, Epoxy Paint, Oil-Resistant Alkyd, Nylon, Delrin, Celcon, PBT

NOT RECOMMENDED:

Neoprene, SBR Rubber, Low Nitrile Buna N, Acrylic Paint, Lacquer, Polystyrene, PVC, ABS

APPLICATION

- Particularly suited for gear applications exposed to extreme service conditions
- All types of enclosed gear drives
- Bearings, including plain rolling elements and antifriction types
- Enclosed gear cases and speed reducers

PROPERTIES	TEST METHOD	ANDEROL 5150 XEP
Appearance @ 20°C	visual	Clear Yellow Liquid
Viscosity @ 40°C, cSt	ASTM D-445	145.1
Viscosity @ 100°C, cSt	ASTM D-445	17.6
Viscosity Index	ASTM D-2270	136
Density @ 15°C, kg/l	ASTM D-1298	0.895
Total Acid Number, mg KOH/g	ASTM D-664	0.4
Flash Point, °C	ASTM D-92	242
Pour Point, °C	ASTM D-97	-45
Foam , Sequence I,II ml	ASTM-892	0
Micro pitting Resistance Test	FVA,54/11	High
FZG Gear test, Pass Stage	DIN/ISO 14635-1	Over 12
Four Ball Wear, 1200 rpm, 40 kg , 75°C	ASTM D-4172	0.35
Four Ball Weld, kg	ASTM D-2783	250

FOR MORE INFORMATION PLEASE REFER TO THE RELEVANT MATERIAL SAFETY DATA SHEET

APPROVALS / REGISTRATIONS



ANDEROL BV

Punterweg 21 A
6222 NW MAASTRICHT
The NETHERLANDS
Tel No.: +31 (0)43 352 41 90
Fax No.: +31 (0)43 352 41 99
www.anderol-europe.com

This information is furnished without warranty, representation, inducement, or license of any kind except that it is accurate to the best of OUR knowledge or obtained from sources believed by ANDEROL to be accurate. ANDEROL does not assume any legal responsibility for use of reliance upon it. Only Chemists or chemically qualified lab technicians should carry out tests. Before using any chemicals, read its label and Material Safety Data Sheet.