

ANDEROL FGH 22

www.Oil18.ru : 902313@inbox.ru : tel (3412) 902-313

H1 High Performance Food Grade Hydraulic Lubricant

Product Data Sheet



ANDEROL FGH 22 is synthetic Hydraulic oil based on a mixture of specially selected non-toxic synthetic polyalphaolefins combined with a high performance additive Technology.

ANDEROL FGH 22 meets the lubrication requirements of Hydraulic systems running in food processing plants.

ANDEROL FGH range is available in the grades ISO VG 32, 46, 68 and 100.

ANDEROL FGH 22 is NSF/H1 and InS/H1 registered. The product is certified Kosher by the Orthodox Union and Halal by the Islamic Food Council of Europe.

ANDEROL Food Grade Lubricants meet the requirement of the FDA regulation 21 CFR 178.3570.

ADVANTAGES / BENEFITS

- Fewer oil changes
- Compatible with hydraulic seals, gaskets, hoses and air system components
- Reduced varnish lacquering and deposits
- Less maintenance intervals
- Lower oil consumption
- Excellent anti-wear properties
- Rust and oxidation inhibited
- Good water separation

COMPATIBILITY

ANDEROL synthetic hydrocarbon based lubricants are similar to mineral oils in their compatibility with paints, seals, gaskets and hoses. No special precautions related to compatibility are required when changing over from a mineral oil lubricant to an **ANDEROL** synthetic hydrocarbon based lubricant.

APPLICATION

Recommended for hydraulic systems in Food processing machinery. Also recommended for chains, vanes, canning and bottling machinery.

Nominal Operating Range is -35/-40°C to 170°C.

APPROVALS

- Unilever

PROPERTIES	TEST METHOD	ANDEROL FGH 22
Appearance @ 20°C	visual	Clear colorless to light yellow liquid
Viscosity @ 40°C, cSt	ASTM D-445	22.2
Viscosity @ 100°C, cSt	ASTM D-445	4.6
Viscosity Index	ASTM D-2270	125
Density @ 15°C, kg/l	ASTM D-1298	0.830
Total Acid Number, mg KOH/g	ASTM D-664	0.06
Flash Point, °C	ASTM D-92	232
Pour Point, °C	ASTM D-97	-40
Demulsibility @ 54°C,min	ASTM D-1401	5

FOR MORE INFORMATION PLEASE REFER TO THE RELEVANT MATERIAL SAFETY DATA SHEET

APPROVALS / REGISTRATIONS



ANDEROL BV

Punterweg 21 A

6222 NW MAASTRICHT

The NETHERLANDS

Tel No.: +31 (0)43 352 41 90

Fax No.: +31 (0)43 352 41 99

www.anderol-europe.com

This information is furnished without warranty, representation, inducement, or license of any kind except that it is accurate to the best of OUR knowledge or obtained from sources believed by ANDEROL to be accurate. ANDEROL does not assume any legal responsibility for use of reliance upon it. Only Chemists or chemically qualified lab technicians should carry out tests. Before using any chemicals, read its label and Material Safety Data Sheet.