



ANDEROL PQAA-68 is a white oil based H1 registered general purpose lubricant, combined with high performance additives. It meets most general purpose requirements of machinery. Anderol PQAA range is available in the grades ISO VG 32 , 46 , 68 , 100 & 150 .

ANDEROL PQAA-68 is NSF/H1 and InS/H1 registered. The product is certified Kosher by the Orthodox Union and Halal by the Islamic Food Council of Europe.

ANDEROL Food Grade Lubricants meet the requirement of the FDA regulation 21 CFR 178.3570

ADVANTAGES / BENEFITS

- Product was developed with highly stable white oil
- Product has excellent wear and load carrying capacity
- Rust and oxidation inhibited
- Good water separation

COMPATIBILITY

ANDEROL white oil based lubricants are similar to mineral oils in their compatibility with paints, seals, gaskets and hoses. No special precautions related to compatibility are required when changing over from a mineral oil lubricant to this product.

APPLICATIONS

H1 Food Approved general purpose lubricant suitable for food manufacturing applications where incidental food contact may occur.

Recommended for use in:

- Hydraulic systems and slide ways
- Vacuum pumps and compressors
- Chain lubrication
- Bearings and gears
- Wipe down oil

Can generally be used in all other rotating equipment applications

APPROVALS

- Unilever

PROPERTIES	TEST METHOD	ANDEROL PQAA 68
Appearance @ 20°C	Visual	Clear to slightly hazy liquid
Viscosity @ 40°C, cSt	ASTM D-445	69.5
Viscosity @ 100°C, cSt	ASTM D-445	8.9
Viscosity Index	ASTM D-2270	102
Density @ 15°C, kg/l	ASTM D-1298	0.862
Total Acid Number, mg KOH/g	ASTM D-664	0.5
Flash Point, °C	ASTM D-92	262
Pour Point, °C	ASTM D-97	-9
Demulsibility @ 54°C,min	ASTM D-1401	20

FOR MORE INFORMATION PLEASE REFER TO THE RELEVANT MATERIAL SAFETY DATA SHEET

APPROVALS / REGISTRATIONS



ANDEROL BV
 Punterweg 21 A
 6222 NW MAASTRICHT
 The NETHERLANDS
 Tel No.: +31 (0)43 352 41 90
 Fax No.: +31 (0)43 352 41 99
 www.anderol-europe.com

